

Linssen Yachts Standard Equipment Linssen Grand Sturdy 500 Sedan

Item	Description	Page 1

BASIC DATA

01010.05	Construction Bottom/hull/decks/superstructure	: SPH®(patent pending) (Softchine Prestressed Hul : 6/5/4/5-4 mm.
	Weight/displacement	: $\pm 25.000 \text{ kg} / \pm 25 \text{ m}^3$
01020.05	LOA x beam x draft	: ± 15.50 x 4.65 x 1.20 m.
	Length hull	: ± 14 m.
	Length over deck	: ± 13.90 m.
	Length waterline	: ± 12.95 m.
	Minimum air draft	: ± 2.75 m.
	Headroom FC/saloon	: ± 2.00/2.0.5 m.
01030.13	CE-classification	: B (sea)
	Number of max. recommended persons	:12
13020.32	Engine	: 2x 4 cyl. Yanmar Diesel, type 4JH110
		ZF 25-H / 2,8 : 1
		80.9 kW (110 HP), 3200 rpm
	Alternator	: 2x 125A-12V
03040.01	Fuel tank capacity	: ± 2x 750 ltr.
	Water tank capacity	: ± 720 ltr.
	Holding tank capacity	: ± 400 ltr.
42001.01	Spacious saloon with U-settee, low saloon tab	le and galley at Port side. Folding
	dinette/desk with 2 design stools and inside st SB-side.	teering position including steering bench at
43001.01	Forward cabin with double berth and cupboar	ds, separate toilet and shower compartment.
	Guest cabin with 2 single beds, one bed can be double bed with drawer and linen cupboard	e slided, so it can be used as a
43045.01	Niche on Port side in the forward cabin with p	lexiglas shelves.

1. HULL

1.1 EXTERIOR

11015.01	Hull constructed in accordance with the Linssen Yachts SPH® (patent pending) construction method
11060.03	Linssen e-Variodeck® (electric sliding roof) in the saloon with integrated cassette mosquito screen/blackout blind
11065.02	Longtop, saloondeck width (small), insulated and finished with ceiling and integrated LED dimmer lights.
11068.01	Selfdraining cockpit with functional drain system
11070.01	Integrated cockpit settee U-shaped with teak top
11080.02	Stern door (SB and Port) to bathing platform
11085.02	Doors in the cockpit at Starboard and Port side

1.2 STAINLESS STEEL

12010.01 Polished stainless steel sea rail

Linssen Grand Sturdy 500 Sedan

Item	Description	Page	2
12020.02	Polished stainless steel hinged side ladder integrated into	deck rail (Port and Starboard)	
12030.02	Opening pulpit lockable incl. stainless steel bar		
12050.05	10 x Original Linssen-design stainless steel cleats		
12055.01	2 x Original Linssen-design stainless steel cleats at the batl	ning platform	
12080.01	Stainless steel handrails on saloon deck		
12130.01	Polished stainless steel foldable bathing ladder at bathing with anti-slip profiles)	platform (incl. solid teak steps	
12146.01	Stainless steel coated bathing platform, with solid teak parendering all around and along part of the hull. Bathing platter hull with demountable supports.	· , ,	
1.3 TE	CHNICAL		
13028.01	Air suction vents for engine room integrated in the hull		
13040.01	Linssen "FIS" system (patent Floor Integrated System®) for integral protected loop-up of cables and ductings in the engine compartment		
13070.03	Provisions for simple installation of stabilization system to prevent rolling of the ship. 2 mounting flanges welded in the hull.		
13110.01	Outside shower at bathing platform, with warm and cold water tap		
13150.02	Integrated bow fitting with fixed anchor roller and stainless steel anchor holder		
13155.01	Mooring facility at bow through stainless steel hawse and stainless steel protection strips		
13260.00	Hull provided with holes in Port and SB bollard box aft deck for mounting mooring winches. Holes are blinded with blind flanges.		
13280.01	Waterproof speakers for radio in open cockpit		
13290.03	Heating outlet with adjustable air outlet in cockpit, connected to heating system		
2. COATII	NG		
2.1 CO	ATING & DECK FINISH		
21010.01	L Linssen 2 component Exterior Coating system		
21020.01	Saloon and cabin deck in anti-slip coating	Saloon and cabin deck in anti-slip coating	
21060.01	Non-toxic antifouling suitable for fresh and salt water (Black colour)		
21070.01	Additional 2-component easy-to-clean protective coating in engine compartment		
21090.19	Original Linssen Sand Beige colour scheme:		
	Superstructure and hull : Sand B	<u> </u>	
	Waterline : Dark G	reen	
	Antifouling : Black		
	Rope fender : Beige Canvas and Covers : Sand -	E/129 01907	
	Glass windows saloon, ventilation-/escape hatches: "sumn	F4128 – 01897 ner green" tinted	

Teak floor in the cockpit finished with solid teak frames incl. original Linssen teak

deck on gangways from transom to sliding doors

3

Linssen Yachts Standard Equipment

Linssen Grand Sturdy 500 Sedan

Item Description Page 3. ENGINE COMPARTMENT 3.1 TECHNICAL 31011.23 Linssen Yachts "hydrolubricated" propeller shaft installation 31021.21 Engine/shaft connection through homokinetic coupling and thrust bearing 31025.32 Low noise propellers Bow thruster 400V/7,5 kW. Powered by the generator, long switching time possible, incl. 31034.02 soft start. Bow thruster can deliver a permanent power of 7.5KW and a peak power of 11KW. 31054.02 Stern thruster thruster 400V/7,5kW. Powered by the generator, long switching time possible, incl. soft start. Stern thruster can deliver a permanent power of 7.5KW and a peak power of 11KW. 31080.03 Twin electronic engine controls at steering position 31090.03 Hydraulic steering 31093.02 Stainless steel steering wheel with teak rim, at inside steering position Fuel tanks of advanced design with inspection/cleaning hatch 31145.21 31161.03 Magnetic level gauge in fuel tanks for direct volume indication Yanmar standard fuel filters with water separator and water alarmsensor. 31180.06 31210.02 Remote fuel supply cut-off to engines from dinette settee 31300.01 Linssen Yachts per cabin thermostatically controlled warm water heating with radiators in the forward cabin, guest cabin, dinette/saloon, aft cabin and wheelhouse. 31307.01 Radiator in front cabin toilet compartment. Thermostatically controlled. 31307.02 Radiator in additional front cabin toilet/shower compartment. Thermostatically controlled. Lighting with ir-sensor under cockpit floor 31315.01 31331.01 Entrance engine compartment by folding ladder between the engines. 31700.03 Automatic fire extinguishing in engine compartment Linssen super sound insulation package consisting of a sound absorbent insulation and a 31750.01 non vibration package. 3.2 ON-BOARD WATER SYSTEMS 32010.13 Automatic pressurized water system (incl. solid PVC water tank with inspection/cleaning hatch), incl. level indicator 32020.01 2 Automatic pumps including expansion reservoir for water system 32050.04 Hot water system (60 litre calorifier) 230 V./800W immersion heater in calorifier 32060.01 Holding tank toilet including Dockside-Discharge connection and level indicator 32080.06 Holding tank capacity All grey water outlets (sinks and shower-drainage) discharge directly overboard 32095.01 Drain pump(s) shower(s) finished with switch-off delay 32110.02 Holding tank waste pump-out unit for Direct Discharge, equipped with timer, so pump switches off automatically after 10 min. 32150.04 Deck-wash pump, including hose and trigger nozzle with connection at bathing platform 32190.01 Electric bilge pump installations placed in bilges of aft cabin, forward cabin and engine room. Equipped with float switch & alarm (3x 100L/min. pumps)

Additional loose electric bilge pump provided, with discharge tube and supply cable

4

Linssen Yachts Standard Equipment

Linssen Grand Sturdy 500 Sedan

Description **Item** Page 3.3 ELECTRICAL & ELECTRONICS 33020.01 Electric domestic 12 V. with automatic main fuse and separate fuses for all users 33022.01 Linssen Yachts ICCESS main switchboards, 1x in saloon and 1x at steering position, for control of key functions and reading of fluid levels 33030.01 230V. /16Amp shore power connection, incl. galvanic insulator, earth leakage circuit breaker and automatic fuse protected end groups with indication and shore power cable (25 metres) 33180.02 Starting circuit 12V. with 2 x maintenance free AGM-battery. 33090.03 Domestic 12V with 4 Lithium Iron Phosphate (LFP) batteries 200Ah. 12 V service net with 1 x maintenance-free "Super Cycle" AGM battery 170 Ah. for 33225.01 anchor winch, mooring winches and hydraulic lowering bathing platform. 33229.01 Domestic net equipped with remote-controlled main switch Automatic battery charger/invertor type Victron Quattro 12/3000 with battery monitor. The 33271.03 battery charger has a maximum charging current of 120A, the maximum output power of the inverter is 3000W. 33285.70 Group of solar panels of 6x 160Wp on part of the longtop. Connected to a Victron Smart Solar charge controller for charging the domestic batteries. Can be read out on the Victron Color GX panel. Generator Northern Lights 400 V/16,0 kW. Priority switch shore power/generator and 33295.05 reverse. Start/stop on steering position. 3.4 INSTRUMENTS & NAVIGATION 34010.02 2 x engine instrument panels with rev.counter, engine hour meter and multifunction meter with voltmeter with alarm, temperature gauge with alarm and oil pressure gauge with alarm 34030.02 Compressor horn with control at steering position 34050.02 Government approved LED navigation lights: Starboard and Port side on superstructure, stern light, top light in mast and anchor light 3.4.1 NAVIGATION INSTRUMENTS Raymarine autopilot with p70RS display at steering position (incl. course computer/rudder 34110.10 indicator/compass transducer) with protection in mast which disengages autopilot during AUTO operation if mast is folded. Raymarine Axiom+12RV, 12" multifunctional colour display with touchscreen and Wi-Fi at 34125.07 steering position. Including read out from echosounder, log and outside water temperature. 34132.80 Raymarine RMK-10 remote keypad for complete touch control for Axiom display. Navionics Gold XL9 marine chart type 46XG, West Europe 34140.03 3.4.5 COMMUNICATION PACKAGES 34190.09 Raymarine Ray90 VHF with Class D "Digital Selective Calling" (DSC) at steering position including antenna in Mast 3.4.6 OTHER NAVIGATION INSTRUMENTS 34135.06 Second Raymarine Axiom+12, 12" multifunctional colour display with touchscreen and Wi-Fi at steering position. Including read out from echosounder, log and outside water temperature. 3.5 EXTERIOR EQUIPMENT HULL

Magnesium or zinc anodes (depending on cruising area)

Linssen Grand Sturdy 500 Sedan

Item	Description	Page
35030.	O1 Original Linssen synthetic-fibre rope fender, with stainless steel stretcher (Beige colou	r)
35040.	O1 Ships name on bow and stern. Port of Registry and Registration number on stern in	
	colour of the waterline	
25000	Bow letter type; Snell Roundhand. Stern letter type; VAG	
35090.	steel anchor rolls, anchor rail and deck switches.	SS
35120.		
35140.	50m. x 10mm. anchor chain, according DIN 766	
3.7 E	EXTERIOR EQUIPMENT SUPERSTRUCTURE	
37030.	O2 Stainless steel windscreen wiper installation in saloon SB and middle, with touch cont suitable for 2 speeds, self-parking, 3- positions interval on 25, 50 and 75% and wish-wash. Incl. integrated choice for synchronise the windscreen wipers at low speed	
37060.	02 Window spray-installation saloon for two wipers	
37070.	Original Linssen Design mast, with double yard, on saloon deck powder coated in superstructure colour, finished with "eyes" and cleats between the yards for flag lines	
37075.	O2 Stainless steel mast stays with quick release system	
37080.	O8 Electric mast lowering system, incl. control at steering position.	
37230.	Fixed luxury teak table with 2-piece folding joint with quick release at bench on aft deck with stainless steel base.	
37270.	Bifold Vario Doors, 4-parts. Aluminium powder-coated door party, double-glazed over entire height. Wicket door on SB side of centre	the
37272.	"Linssen slide and pop-out-door (LSP®)", watertight sliding door in saloon on port and SB-side, coated in superstructure colour, with special lip-seal developed by Linssen	
3.8 V	VINDOWS	
38030.	Double-glazed "Summer Green" tinted windows in the saloon with thermal insulated profile (Thermic Line).	
38060.	Front hinged window Port side with green tinted glass in the saloon, can be opened and closed electrically. With grey thermal insulated profile (Thermic Line). Incl. mosqu screen, fitted on the outside with magnets	ito
38300.	7x opening port-holes in the forward cabin, with plain acrylate and in the FC cupboard 1x fixed porthole	
38405.	2x Aluminium ventilation/escape hatch, with clear acrylic in the forward cabin, incl. bl rouleau/curtain with integrated screen.	ind
38412.	O1 Aluminium ventilation/escape hatch, clear acrylic in centre cabin and toilet compartm with blackout blind and integrated insect screen	ent,
4. INTE	RIOR	
GEN	ERAL	
40010.	01 Linssen panels FPS® (Floating Panel System, Patented)	
40020.	O3 Interior constructed of high-end okoumé panelling with cherry finish	
40025.	14 Interior and exterior style "Classic Traditional": Classic modesty. Stylish elegance throusoft beige shades.	ıgh
40030.	02 Deck-head lining in elegant vinyl finish panels	
40040.		
40050.	O2 High gloss stainless steel fittings in all compartments	
40000		

High gloss stainless steel door and locker furniture, with push-button catches

Linssen Grand Sturdy 500 Sedan

Description

Item

em	Description	Page	6
4.1 C	PEN COCKPIT		
41141.9	Storage system under the cockpit floor. Executed as cabinet wall 3 modules on S and 3 modules at Port side. Including 8 plastic storage boxes 400x300x200mm a folding crates 400x300x200mm.		
4.2 S	ALOON & GALLEY		
42011.	Hatch above engine room for easy access and inspection of this room.		
42021.0	Comfortable U-shaped saloon settee with integrated storage space. The rear sea position of the saloon settee can be rotated by 180 degrees so that it can be used as both an indoor and outdoor seat.	iting	
42035.0	D3 Elegant saloon table, low model		
42037.0	O1 Saloon table top with flush leather panel.		
42061.	Walnut wood dashboard finished in real leather, at SB side		
42081.	01 U-shaped galley with cupboards and drawers		
42092.	U-shaped galley worktop finished with original Corian®		
42141.0	Punctional storage space in forward section, equipped with 6 storage boxes and	lighting	
4.3.1	FRONT CABIN AND GUEST CABIN		
43010.	O1 Stylish/high quality flooring in front cabin on second floor level next to bed.		
43021.0	Double berth with slatted base and 2 drawers		
43043.0	Large wall cabinet in the FC on the SB side. The cabinet is equipped with automatic lighting, adjustable and removable shelves and fiddle rails.		
43102.0	Two single berths in the guest cabin, incl. drawer under Stbd berth. The beds can be converted into one double bed	า	
43121.0	O1 Spacious linen cupboard in guest cabin		
4.3.2	SHOWER AND HEADS COMPARTMENTS		
43062.	Toilet/shower walls FC in high quality Formica wall finishing		
43071.	Integrated washbasin surface mounted in front toilet-compartment vanity unit. finished in original Corian®	Worktop	
43082.0	Shower in the FC finished in high quality HPL wall finishing		
43082.	Shower tray front cabin in corian designed with grooves for water drainage		
43082.0	O1 Guest shower at portside in the FC finished in HPL finish		
43081.	11 Storage space in the toilet compartment FC		
43081.	Corian shower tray in guest wet room in the forward cabin, 3-dimensionally shap optimal water drainage.	ped for	
43081.	Integrated washbasin surface mounted in front toilet-compartment vanity unit. finished in original Corian®	Worktop	
43200.0	Shower in guest bathroom with built-in Grohe shower mixer, thermostatically co- including sliding wall bar. 3-dimensionally shaped Corian shower tray for optima drainage.		

Linssen Grand Sturdy 500 Sedan

Item	Description Page	7
5. FINISI	н	
5.1 LI	IGHTING & SOCKETS	
51010.0	D5 LED interior lighting with wall switches and/or switch on light point in the	
	compartments. Dimmable LED lighting in front cabin, guest cabin and saloon.	
51080.1	11 Luxurious LED reading lights (2x) in the front cabin	
51090.1	11 Luxurious LED reading lights (2x) in the guest cabin	
51100.0	Attractive indirect lighting in the FC, AC and in the hall to the aft cabin	
51100.0	O2 Attractive indirect lighting in the FC heads	
51400.1	USB-connection in saloon (2x), steering position (1x), dinette/desk (1x), FC (1x) and guest cabin (1x) for charging mobil equipment. (Total 6x)	
51500.0	1 x 12 V. socket in the saloon on Starboard-side, aft	
51601.0	230 V. sockets in the FC (2x), guest cabin (1x), toilet FC (1x), guest toilet (1x), saloon (4x), galley (1x double) and steering position (1x). (Total 12x)	
51640.0	O1 Additional 1x double 230 V. socket in the galley	
5.2 G	ALLEY	
52015.0	Bar cupboard/drawer in saloon, incl. set of Linssen Yachts glasses (comprising: 6 shot glasses, 6 highball glasses, 5 whisky glasses, 6 wine glasses and 6 champagne glasses)	
52020.0	O1 Integrated waste bucket in cupboard	
52025.0	Plate holders and anti-skid mats in galley drawers	
52029.0	In the galley 2 drawers next to oven	
52030.0	O1 Cutlery tray	
52034.0	Pharmacy cabinet in the galley	
52035.0	"Magic Corner" cupboard including basket set in saloon under the steering seat.	
52040.0	80 l. refrigerator with freezer compartment under the steering bench, accessible from the galley.	
52050.0	110 Ltr. refrigerator with freezer compartment in saloon	
52080.0	230V. dishwasher (front loader) integrated into galley. Capacity: 6 covers	
52100.0	230V. washer/dryer combination, fitted in the guest head forward cabin SB-side	
52140.0	230V. induction hob, stainless steel, with touch control. 1 x 1200 W. cooking zone, 2 x 1800 W. cooking zone, 1 x 2200 W. cooking zone	
52180.0	O1 Stainless steel/corian sink	
53020.0	1 3 7 71	
52220.0	230V. stainless steel 42 l. microwave/oven/grill combination. Temperature range 30-250 degrees. 90-1000W microwave power	
5.3 S/	ANITARY FITTINGS	
53010.0	Selected bathroom fittings (mirror, toilet paper holder, etc.), in the forward cabin head	
53010.1	In the FC bathroom cabinet integrated 6-litre waste bin with stainless steel soft-close waste flap	
53012.0	Selected bathroom fittings (mirror, toilet paper holder, etc.), in guest head	
53012.1	In the guest bathroom cabinet integrated 6-litre waste bin with stainless steel soft-close waste flap	
53030.0	Build in wall mixer tap in toilet compartment FC, chrome, type Grohe Talis	

Build in wall mixer tap in forward shower type Grohe (Thermostatically adjustable) incl.

53050.06

shower rail

Linssen Grand Sturdy 500 Sedan

tem	Description	Page	8
53130.0	D2 Electric toilet in forward cabin, with fresh water rinsing		
53135.0	2 Electric Deluxe Flush toilet, with fresh water rinsing in guest head		
53130.9	"Odour system" to reduce smells from black water system		
5.4 A	UDIO / VIDEO / INTERNET		
54010.0	Stereo radio/MP3-player Fusion Apollo Apollo RA770 with bluetooth and touch so including Subwoofer and 2 speakers in the saloon and amplified radio-antenna in t mast, connected to Raymarine display. Radio can be controlled via Fusion app on sphone or tablet	the	
54200.0	Primary TV connection at saloon under steering position, incl. extra 230 V. socket		
54250.0	Glomex TV-antenna on mast, suitable for analogue & digital reception. Suitable for DVBT-T2 network.		
54400.0	43" (109cm) LED TV with integrated DVB-T2 & DVB-S tuner in saloon		
54500.0	Electric TV lift integrated in salon furniture, TV lift control with remote control		
5.6 IN	NTERIOR UPHOLSTERY		
56041.0	22 Anatomically moulded U-shaped saloon settee, finished in genuine leather		
56045.5	Comfortable electrically horizontally adjustable Linssen Design helm seat with mat leather upholstery.	ching	
56050.0	Dashboard finished in genuine leather		
56073.2	22 2 design stools finished in genuine leather.		
56101.0	Mattrass 2x 1 pers.in front cabin type 7-zone 14 cm.		
56161.0	Mattrass 2x single person in guest cabin type coldfoam 10 cm. with layer in foam in two hardness grades.		
56300.0	Beautiful pleated window covering manually operated for windows and port holes throughout the ship	i	
5.7 E	XTERIOR UPHOLSTERY		
57031.0	Cushion set for U-shaped cockpit settee in in water-repellent fabric, colour depend chosen interior package	ling on	
5.8 E	QUIPMENT		
58010.0	Spares kit including tool-kit, impeller, fuses, paint-tip and various maintenance par	ts	
58020.0	Complete inventory including 6 fenders, 4 mooring ropes (16 meters), boathook, li buoy, bucket, scrubbing brush, national flag, yard burgee, safety rope for anchor cand anchor ball		
58030.0	Pirst-aid box in saloon according to DIN13157		
58040.0	ABC fire class compliant fire extinguishers (3 x 2 kg)		
58045.0	Optical smoke detector with fixed built-in lithium battery (life span 10 years) in all sleeping compartments.		
5.9 C	ANVAS & COVERS		
59020.1	L1 Cockpit canvas Longtop, beige.		
59021.0	21 Linssen One Touch Cockpit Cover (OCC)®:		
	This electric cockpit cover, developed and patented by Linssen, can be opened all around the cockpit. By opening a zip and a few push buttons, the entire canvas (in 2 parts, SB and Port) can be opened and closed automatically by remote control. T sails disappear into the Linssen design powder-coated aluminium storage cassette SB and Port side of the cockpit.	he	