

### Linssen Yachts Standard Equipment

## Linssen Grand Sturdy 45.0 Sedan Intero

ltem D	escription	Page 1
BASIC DAT	4	
01010.05	Type code Construction Bottom/hull/decks/superstructure Weight/displacement	: 11D : SPH®(patent pending) (Softchine Prestressed Hu : 6/5/4/4 mm. : ±19.500 kg / ±19,5 m <sup>3</sup>
01020.05	LOA x beam x draft Length over deck Length waterline Minimum air draft Headroom FC/saloon	: ± 13.98 x 4.35 x 1.20 m.(single engine version) : ± 13.98 x 4.35 x 1.22 m. (twin engine version) : ± 13.23 m. : ± 12.00 m. : ± 2,72 m. : ± 1.97/2.01 m.
01030.03	CE-classification Number of max. recommended persons	: B (sea) : 10
03040.01	Fuel tank capacity Water tank capacity Holding tank capacity	: ± 1x 1080 ltr. : ± 440 ltr. : ± 300 ltr.

#### 1. HULL

#### **1.1 EXTERIOR**

- 11015.01 Hull constructed in accordance with the Linssen Yachts SPH<sup>®</sup> construction method
- 11065.02 Longtop, saloondeck width, insulated and finished with ceiling and integrated LED dimmer lights.
- 11068.01 Selfdraining cockpit with functional drain system
- 11070.01 Integrated cockpit settee L-shaped with teak top
- 11080.01 Integrated stern door to bathing platform

#### **1.2 STAINLESS STEEL**

- 12010.01 Polished stainless steel sea rail
- 12020.01 Side entrances with stainless steel entrance chains
- 12030.01 Opening in sea rail at the bow (lockable with stainless steel chain)
- 12050.03 8 x Original Linssen-design stainless steel cleats
- 12055.01 2 x Original Linssen-design stainless steel cleats at the bathing platform
- 12080.01 Stainless steel handrails on saloon deck
- 12120.01 Settee with storage space and solid teak top on bathing platform
- 12125.01 Teak step in side decks
- 12130.01 Polished stainless steel foldable bathing ladder at bathing platform (incl. solid teak steps with anti-slip profiles)
- 12145.02 Robust, stainless steel coated bathing platform, with solid teak parts (including Heavy Duty Linssen PVC fendering from bathing platform to 1/3 of the hull length)

#### **1.3 TECHNICAL**

13010.33 Engine

: 1x 4 cyl. Yanmar Diesel, type 4LV150 ZF 68 / 2,783 : 1 110 kW (150 HP), 3500 rpm : 130A-12V

# Linssen Yachts Standard Equipment

## Linssen Grand Sturdy 45.0 Sedan Intero

#### Item Description

Page 2

- 13030.01 Linssen DUAL CROSS engine foundation
- 13040.01 Linssen "FIS" system (patent Floor Integrated System<sup>®</sup>) for integral protected loop-up of cables and ductings in the engine compartment
- 13061.04 Provisions for sternthruster incl. main power cables
- 13080.03 Provisions for deck-wash pump
- 13110.01 Outside shower at bathing platform, with warm and cold water tap
- 13150.02 Integrated bow fitting with fixed anchor roller and stainless steel anchor holder
- 13240.01 Selfdraining seawaterproof anchor chain container
- 13270.02 Provisions for installation of a Linssen tender lift at bathing platform
- 13280.01 Waterproof speakers for radio in open cockpit

### 2. COATING

#### 2.1 COATING & DECK FINISH

- 21010.01 Linssen 2 component Exterior Coating system
- 21020.01 Saloon and cabin deck in anti-slip coating
- 21030.01 Fore-deck and side decks in anti-slip coating
- 21060.01 Non-toxic antifouling suitable for fresh and salt water (Black colour)
- 21070.01 Additional 2-component easy-to-clean protective coating in engine compartment
- 21090.19 Original Linssen colour scheme:
  - Superstructure and hull
  - Waterline
  - Antifouling
  - Rope fender Canvas and covers

- : Sand Beige : Dark Green
- : Black
- : Beige
- : Sunbrella Marine
- Beige Papyrus
- : "summer green" tinted

Glass windows saloon

#### 2.2 TEAK DECKS

22030.01 Teak floor in the cockpit

#### **3. ENGINE COMPARTMENT**

#### **3.1 TECHNICAL**

- 31010.23 Linssen Yachts "hydrolubricated" propeller shaft installation
- 31020.21 Engine/shaft connection through homokinetic coupling and thrust bearing
- 31025.31 Special low noise propeller
- 31032.09 Electric bowthruster Sleipner-Side power 24V/170 kgf (8 kW / 10,7 HP) incl. 2x 170 Ah maintenance-free batteries
- 31070.05 Electronic engine control at steering position
- 31093.02 Stainless steel steering wheel with teak rim, at inside steering position
- 31120.01 Emergency steering installation
- 31150.13 Central positioned fuel tank with inspection/cleaning hatch, incl. level indicator (± 1080 litres)
- 31160.03 Magnetic level gauge in fuel tank for direct volume indication
- 31170.05 Separate second (1x on engine) fuel filter, with water separator
- 31210.01 Fuel supply cut-off to engine from saloon settee
- 31240.05Linssen Compartment Controlled Heating with separate day/night function: 1x 5.5 kW warm<br/>air heating. For saloon, galley with control in saloon and 1x 4 kW for FC/toilet and<br/>guest cabin with control in the FC. Lockable outlets in guest cabin/toilet compartment

### Linssen Yachts Standard Equipment

### Linssen Grand Sturdy 45.0 Sedan Intero

#### Item Description Page 3 31310.01 Engine room lighting with switch and indicator in switch panel Engine compartment hatch, with a ladders next to the engine 31330.01 31700.03 Automatic fire extinguishing in engine compartment Linssen super sound insulation package consisting of a sound absorbent insulation and a 31750.01 non vibration package. **3.2 ON-BOARD WATER SYSTEMS** 32010.02 Automatic pressurized water system (incl. solid PVC water tank with inspection/cleaning hatch (± 440 litres), incl. analogue level indicator in switch panel) 32020.01 2 Automatic pumps including expansion reservoir for water system 32050.04 Hot water system (60 litre calorifier) 32060.01 230 V./800W immersion heater in calorifier 32080.03 Holding tank toilet including Dockside-Discharge connection and level indicator (± 300 litres) 32095.01 All grey water outlets (sinks and shower-drainage) discharge directly overboard Drain pump(s) shower(s) finished with switch-off delay 32110.02 Holding tank waste pump-out unit for Direct Discharge 32180.02 Electric bilge pump installation in engine compartment, with float switch for alarm. Manually switched. Bilge pump capacity: 100L/min. 32200.01 Additional loose electric bilge pump provided, with discharge tube and supply cable **3.3 ELECTRICAL & ELECTRONICS** 33022.01 Linssen Yachts ICCESS main switchboards, 1x in saloon and 1x at steering position, for control of key functions and reading of fluid levels 33030.01 230V. /16Amp shore power connection with fuses and shore power cable (25 metres) 33050.21 Shore power connection equipped with a galvanic insulator for an optimal separation between domestic & shore power 33082.03 Domestic: 12V. with 3 maintenance free Gel batteries 166 Ah. 33180.01 Starting circuit 12V. with 1 x maintenance free AGM-battery. 33230.03 Additional battery charger for bow and sternthruster group 33271.03 Automatic battery charger/invertor type Victron Quattro 12/3000 with battery monitor. The battery charger has a maximum charging current of 120A, the maximum output power of the inverter is 3000W. 33285.60 Group of solar panels of 4x 110Wp. Connected to a Victron Smart Solar charge controller for charging the domestic batteries. Can be read out on the Victron Color GX panel. **3.4 INSTRUMENTS & NAVIGATION** 34010.21 Engine instrument panel with rev.counter, voltmeter with alarm, temperature gauge with alarm, oil pressure gauge with alarm, ignition key and engine hour meter

- 34030.02 Compressor horn with control at steering position
- 34050.02 Government approved LED navigation lights: Starboard and Port side on superstructure, stern light, top light in mast and anchor light
- 34070.01 Spare wiring for compass/windset

#### **3.4.1 NAVIGATION INSTRUMENTS**

34080.14 Raymarine i70S multifunction instrument with read out from echosounder, log and outside water temperature at steering position

# Linssen Grand Sturdy 45.0 Sedan Intero

### Linssen Grand Sturdy 45.0 Sedan int

#### **3.5 EXTERIOR EQUIPMENT HULL**

Description

Item

- 35010.00 Magnesium or zinc anodes (depending on cruising area)
- 35030.01 Original Linssen synthetic-fibre rope fender, with stainless steel stretcher (Beige colour)
- 35040.01 Ships name on bow and stern. Port of Registry and Registration number on stern in colour of the waterline

Bow letter type; Snell Roundhand. Stern letter type; VAG

35081.23 Manual anchor winch with integrated Heavy Duty stainless steel anchor roller and Linssen patented anchor rail. Including 30m 8mm. anchorchain and 20 kg. Bruce anchor

#### **3.7 EXTERIOR EQUIPMENT SUPERSTRUCTURE**

- 37030.02 Robust windscreen wiper installation saloon, position middle and Port
- 37060.02 Window spray-installation saloon for twee wipers including wish-wash function
- 37070.04 Original Linssen Design mast, with double yard, powder coated in superstructure colour
- 37075.02 Stainless steel mast stays with quick release system
- 37180.01 Stainless steel Linssen Grand Sturdy logo
- 37210.01 Cockpit hatch equipped with stainless steel lock and gas strut
- 37271.11 Entrance doors, varnished in superstructure colour
- 37272.11 "Linssen slide and pop-out-door (LSP<sup>®</sup>)", watertight sliding door in saloon on port-side, coated in superstructure colour, with special lip-seal developed by Linssen

#### **3.8 WINDOWS**

- 38010.01 All windows to saloon in anodised aluminium profiles, incl. toughened "Summer Green" tinted glass
- 38040.02 Hinged Starboard window in forward saloon, with "summer green" tinted glass
- 38300.06 6 x opening port-holes in the forward cabin, with plain acrylate
- 38405.01 Aluminium ventilation/escape hatch with clear acrylic in front cabin.
- 38412.01 Aluminium ventilation/escape hatch, clear acrylic in centre cabin and toilet compartment.

#### **4. INTERIOR**

#### GENERAL

40010.01 Linssen panels FPS® (Floating Panel System, Patented)
40020.03 Interior constructed of high-end okoumé panelling with cherry finish
40030.02 Deck-head lining in elegant vinyl finish panels
40040.01 Original Linssen maintenance friendly ship's floor, wengé color. Hatches in aisle to FC finished with hinges
40050.02 High gloss stainless steel fittings in all compartments
40060.02 High gloss stainless steel door and locker furniture, with push-button catches

#### **4.1 OPEN COCKPIT**

- 31740.00 Cockpit basement constructed with wooden floor section midships against engine room bulkhead
- 31740.01 Access to storage space underneath the cockpit floor (with ladder)

#### 4.2 SALOON & GALLEY

- 42021.01 Comfortable U-shaped saloon settee with "Easy Sleep Convert System", double-bed function with integrated storage space
- 42035.03 Elegant saloon table, low model

4

5

Page

### Linssen Yachts Standard Equipment

### Linssen Grand Sturdy 45.0 Sedan Intero

#### Item Description

- 42061.01 Steering position with side-adjustable and longitudinally helmseat
- 42081.01 U-Shaped galley with cupboards and drawers
- 42092.01 U-shaped galley worktop finished with original Corian<sup>®</sup> "Clamshell"
- 42099.99 Additional work surface in the galley through folding part next to hob
- 42141.01 Functional storage space in forward section with automatic light switch
- 42414.01 Wall panels in saloon SB, Port and front in cream white HPL.

#### 4.3.1 FRONT CABIN AND GUEST CABIN

- 43021.01 Double berth with slatted base and 2 drawers
- 43031.01 Combined hanging-locker/linen-cupboard on Port side
- 43041.02 Spacious linen cupboard on Starboard side
- 43101.01 Two single berths in the guest cabin, incl. drawer under Stbd berth
- 43121.01 Spacious linen cupboard in guest cabin
- 43111.01 Cupboard between the berths in guest cabin
- 43412.02 Soft paneling FC, longitudinal SB/Port (4 panels)

#### 4.3.2 SHOWER AND HEADS COMPARTMENTS

- 43062.01 Toilet/shower walls FC in HPL finish
- 43071.02 Washbasin in front toilet-compartment, built into vanity unit. Worktop and wash basin in toilet compartment finished in original Corian<sup>®</sup> "Clamshell"
- 43082.01 Guest shower at portside in the FC finished in HPL finish
- 43082.91 Shower trays in corian type Clamshell designed with grooves for water drainage, without skirting boards
- 43081.11 Storage space in toilet compartment for guests, suitable for subsequently fitting of washer/dryer

#### 5. FINISH

#### **5.1 LIGHTING & SOCKETS**

- 51010.05 LED dimmed interior light fittings in all compartments, with light switches
- 51080.11 Luxurious LED reading lights (2x) in the front cabin
- 51110.05 Indirect lighting in step to galley
- 51400.01 1x USB socket in the saloon for charging mobil equipment. No data transfer.
- 51500.00 1 x 12 V. socket at dinette in saloon
- 51600.01 230 V. Sockets in the FC (1x), toilet FC (1x), guest toilet (1x), saloon foding table (1x) and galley (3x)

#### 5.2 GALLEY

- 52015.01 Bar cupboard in saloon, incl. set of Linssen Yachts glasses (comprising: 6 shot glasses, 6 highball glasses, 6 whisky glasses and 6 wine glasses)
- 52020.01 Integrated waste bucket in cupboard
- 52025.01 Anti-skid mats in galley drawers
- 52030.01 Cutlery tray
- 52034.01 Pharmacy cabinet in the galley
- 52040.02 110 l. refrigerator with freezer compartment in the galley
- 52105.02 Gas installation with Campingaz gas bottle (3kg), in container at bathing platform
- 52110.02 3-burner stainless steel gas hob
- 52120.02 Glass coverplate for 3-burner gas hob

# Linssen Grand Sturdy 45.0 Sedan Intero

# Item Description Page

52180.01 Stainless steel sink

53020.03 Mixer tap in galley type Grohe Essence

### **5.3 SANITARY FITTINGS**

- 53010.01 Selected bathroom fittings (mirror, toilet paper holder, etc.), in the forward cabin head
- 53015.01 Selected bathroom fittings (mirror, toilet paper holder, etc.), in the toilet compartment for guests
- 53030.03 Wash-basin mixer tap in toilet compartment FC type Grohe Essence
- 53035.03 Wash-basin mixer tap in toilet compartment cabin type Grohe Essence
- 53050.04 Shower mixer tap in forward shower type Grohe 1000C (Thermostatically adjustable) incl. shower rail
- 53130.02 Electric toilet in forward cabin, with fresh water rinsing
- 53130.99 "Odour system" to reduce smells from black water system
- 53135.02 Electric toilet with fresh water rinsing in second toilet compartment front cabin

### 5.4 AUDIO / VIDEO

54010.02 Stereo radio/MP3-player Fusion RA70N with bluetooth including 2 speakers in the saloon and FM radio antenna in mast. Audio streaming possible Operation possible via the App FUSION link AM/FM including RDS Amplifier Class-AB 4x 50W

### **5.6 INTERIOR UPHOLSTERY**

- 56041.02 Anatomically moulded U-shaped saloon settee, finished in genuine leather, cream colour
- 56045.02 Comfortable steering bench at inside steering position, finished in genuine leather, cream colour
- 56073.22 2 design stools finished in genuine leather, cream color
- 56101.11 Mattrass 1x 2 pers. in front cabin type coldfoam 14 cm. with layer in foam in two hardness grades.
- 56161.01 Mattrass 2x single person in guest cabin type coldfoam 10 cm. with layer in foam in two hardness grades.
- 56300.01 Luxurious curtains for windows and hatches saloon and FC, cream colour

### **5.7 EXTERIOR UPHOLSTERY**

57030.03 Cushions for cockpit bench in imitation leather colour Sand beige

### 5.8 EQUIPMENT

- 58010.01 Spares kit including tool-kit, impeller, fuses, paint-tip and various maintenance parts
- 58020.01 Complete inventory including 6 fenders, 4 mooring ropes (10 meters), boathook, life buoy, bucket, scrubbing brush, national flag, yard ribbon, safety rope for anchor chain and anchor ball
- 58030.01 First-aid box in saloon according to DIN13157
- 58040.01 ABC fire class compliant fire extinguishers (2 x 2 kg): 1x in saloon settee, 1x in "cellar"
- 58045.01 Optical smoke detector with fixed built-in lithium battery (life span 10 years) in all sleeping compartments.

### 5.9 CANVAS & COVERS

59020.16 Cockpit canvas Longtop Sunbrella Marine Beige Papyrus. The side and back panels can be opened seperately by a zip-fastener

age 6