

Linssen Yachts Standard Equipment Linssen 30 SL Sedan

Item	Description	Page	1
icciii	Description	rage	

DASIC DAIA		
01010.05	Type code Construction Hull Decks/superstructure Weight/displacement	: 01J : HPH (Hardchine Prestressed Hull) : 5/4 mm. : 4 mm. : ± 7.500 kg / ± 7,5 m3
01020.05	LOA x beam x draft Length over deck Length waterline Minimum air draft Headroom FC/saloon	: ± 9.70 x 3.35 x 1.00 m. : ± 8.87 m. : ± 7.83 m. : ± 2.37 m. : ± 1.83/1.94 m.
01030.02	CE-classification Number of max. recommended persons	: C (coast) : 8
13010.19	Engine	: 1x 4 cyl. Volvo Penta Diesel, type D2-50 ZF 25-H / 2,8 : 1 1x 37.5 kW (51 HP), 3000 rpm
	Alternator	: 115A-12V
03040.01	Fuel tank capacity Water tank capacity Holding tank capacity	: ± 240 ltr. : ± 220 ltr. : ± 240 ltr.
42001.01	Spacious saloon with L-settee (incl. Easy Sleep Comfortable helmseat, longitudinally adjustable with Design stool at Port side.	• • •
43001.01	Front cabin with double berth with slatted base, separate shower compartment.	cupboards, toilet compartment and

1. HULL

1.1 EXTERIOR

11015.01	Hull constructed in accordance with the Linssen Yachts HPH® construction method	
11065.02	Longtop, saloondeck width, insulated and finished with ceiling and integrated LED dimmer lights.	
11068.01	Selfdraining cockpit with functional drain system	
11070.01	Integrated cockpit settee with teak top	
11080.01	Integrated stern door to bathing platform	
1.2 STAINLESS STEEL		
12010 01	Polished stainless steel see rail	

12010.01	Polished stainless steel sea rail
12020.01	Side entrances with stainless steel entrance chains

12030.01	Opening in sea rail at the bow (lockable with stainless steel chain)

12050.02 6 x Original Linssen-design stainless steel cleats

12055.01 2 x Original Linssen-design stainless steel cleats at the bathing platform

12080.01 Stainless steel handrails on saloon deck

Linssen 30 SL Sedan

Item I	Description	Page	2
12125.01	Teak step in side decks		
12130.01	Polished stainless steel foldable bathing ladder at bathing platform (incl. solid teak swith anti-slip profiles)	steps	
12145.02	Robust, stainless steel coated bathing platform, with solid teak parts (including Hear Duty Linssen PVC fendering from bathing platform to $1/3$ of the hull length)	vy	
1.3 TEC	HNICAL		
13030.01	Linssen DUAL CROSS engine foundation		
13040.01	Linssen "FIS" system (patent Floor Integrated System®) for integral protected loop-ucables and ductings in the engine compartment	ıp of	
13060.02	Provisions for sternthruster, incl. main power cables		
13080.03	Provisions for deck-wash pump		
13110.01	Outside shower at bathing platform, with warm and cold water tap		
13150.02	Integrated bow fitting with fixed anchor roller and stainless steel anchor holder		
13240.01	Selfdraining seawaterproof anchor chain container		
13280.01	Waterproof speakers for radio in open cockpit		
2. COATIN	G		

2.1 COATING AND DECK FINISH

21010.01	Linssen 2 component Exterior Coating syste	em	
21020.01	Saloon and cabin deck in anti-slip coating		
21030.01	Fore-deck and side decks in anti-slip coatin	g	
21060.01	Non-toxic antifouling suitable for fresh and salt water (Black colour)		
21070.01	Additional 2-component easy-to-clean protective coating in engine compartment		
21090.25	Original Linssen SL colour scheme:		
	Superstructure and hull	: Egg Shell White	
	Waterline	: SL bow-up design, black	
	Antifouling	: Black	
	Rope fender	: Black	
	Glass windows saloon	: "Smoke Grey" tinted	

2.2 TEAK DECKS

22030.01 Teak floor in the cockpit

3. ENGINE COMPARTMENT

3.1 TECHNICAL

31010.01	Linssen Yachts "hydrolubricated" propeller shaft installation
31020.01	Engine/shaft connection through homokinetic coupling and thrust bearing
31025.01	Special low noise propeller
31030.03	12V. Bowthruster 55 kgf (3 kW / 4 HP)
31070.01	Mechanical Morse engine control equipped with anti-vibration kit for noise and vibration damping.
31090.01	Hydraulic steering
31093.02	Stainless steel steering wheel with teak rim, at inside steering position
31120.01	Emergency steering installation
31150.02	Fuel tank of advanced design with inspection/cleaning hatch (± 240 litres)
31160.03	Magnetic level gauge in fuel tank for direct volume indication

Linssen 30 SL Sedan

tem	Description	Page	3
31170.0	Separate second (1 x on engine) fuel filter with water separator		
31210.0	Fuel supply cut-off to engine from saloon settee		
31240.0	Air-heating 4kW with outlets in saloon and FC (lockable). Control panel in saloon.		
31700.0	Automatic fire extinguishing in engine compartment		
31750.0	Linssen super sound insulation package consisting of a sound absorbent insulation non vibration package.	and a	
3.2 0	N-BOARD WATER SYSTEMS		
32010.0	Automatic pressurized water system including solid PVC water tank with inspection hatch and level indicator (± 220 litres)	n/cleaning	
32020.0	Automatic pump with electronic pressure regulation for water system		
32050.0	Hot water system (24 litre calorifier)		
32060.0	230 V / 500W immersion heater in calorifier		
32080.0	Holding tank toilet including Dockside-Discharge connection and level indicator (\pm litres)	240	
32095.0	All grey water outlets (sinks and shower-drainage) discharge directly overboard		
32110.0	Holding tank waste pump-out unit for Direct Discharge		
32180.0	Electric bilge pump installation in engine compartment, with float switch for alarm Manually operated. Capacity of bilge pump: 61L/min.		
32200.0	Additional loose electric bilge pump provided, with discharge tube and supply cabl	е	
3.3 EI	LECTRICAL & ELECTRONICS		
33020.0	Electric domestic 12 V. with automatic main fuse and separate fuses for all users		
33022.0	Linssen Yachts ICCESS main switchboards, 1x in saloon and 1x at steering position, control of key functions and reading of fluid levels	for	
33030.0	230V. /16Amp shore power connection with fuses and shore power cable (25 metr	res)	
33050.2	Shore power connection equipped with a galvanic insulator for an optimal separation between domestic & shore power	ion	
33082.0	Domestic: 12V. with 1 maintenance free GEL batterie 166 Ah.		
33180.0	Starting circuit 12V. with 1 x maintenance free "Super Cycle" AGM-battery 170 Ah.		
33230.0	Automatic VICTRON BlueSmart 12/30-3 (3x 30 A.) battery charger, with BlueTooth that allows readout via app.	function	
3.4 IN	ISTRUMENTS & NAVIGATION		
34010.0	Engine instrument panel with rev.counter and volt-, temperature and oil pressure a (acoustic en optical)	alarm	
34030.0	Compressor horn with control at steering position		
34050.0	LED navigation lights: Starboard and Port side on superstructure, stern light, top lig mast and anchor light	tht in	
34070.0	Spare wiring for compass/windset		
3.4.1	NAVIGATION INSTRUMENTS		
34080.1	4 Raymarine i70S multifunction instrument with read out from echosounder, log and water temperature at steering position	loutside	
3.5 EX	KTERIOR EQUIPMENT HULL		
35010.0	1 Magnesium anodes (for fresh water)		
35030.0		lour)	
35030.9			

Linssen 30 SL Sedan

tem	Description Page
35081.22	Manual anchor winch with integrated Heavy Duty stainless steel anchor rollers and Linssen patented anchor rail. Including 30m 8mm. anchor chain and 15 kg. Bruce anchor
3.7 EX	TERIOR EQUIPMENT SUPERSTRUCTURE
37030.02	Robust windscreen wiper installation wheelhouse, position middle and SB-side
37070.01	Original Linssen Design mast powder coated in colour superstructure
37075.02	Stainless steel mast stays with quick release system
37182.01	Air suction vents for engine compartment provided with sporty Stainless steel Linssen Design "Sport Luxury" logo
37210.01	Cockpit hatch equipped with stainless steel lock and gas strut
37271.11	Entrance doors, varnished in superstructure colour
3.8 WI	NDOWS
38011.41	Windows saloon in grey colour anodised aluminium profiles, incl. toughened "Smoke grey" tinted glass. Front windows in plain glass.
38060.32	Hinged aluminium Port front window in saloon, with grey profiles and plain glass
38086.32	Sliding window in saloon at SB side front, with grey profiles and "Smoke Grey" tinted glass
38300.32	4 x opening port-holes in the forward cabin, with plain acrylate, profile grey
38401.11	Aluminium ventilation/escape hatch, profile in superstructure colour with "Smoke Grey" tinted glass in the forward cabin
1. INTERI	OR
GENER	RAL
40010.01	Linssen panels FPS® (Floating Panel System, Patented)
40020.03	Interior constructed of high-end okoumé panelling with cherry finish
40030.02	Deck-head lining in elegant vinyl finish panels
40040.01	Original Linssen maintenance friendly ship's floor, wengé color
40050.02	High gloss stainless steel fittings in all compartments
40060.02	High gloss stainless steel door and locker furniture, with push-button catches
4.2 SA	LOON/ GALLEY
42021.01	Comfortable U-shaped saloon settee with "Easy Sleep Convert System", double-bed function with integrated storage space
42031.02	Elegant wider saloon table. Including provision for sea-fixed mounting in the cockpit by means of Bellingham fastenings
42061.01	Steering position including comfortable helmseat, longitudinally adjustable
42082.01	L-Shaped galley with cupboards and drawers
42092.01	Galley worktop finished with "Nimbus Prima" original Corian®
42112.01	Chart table/desk with folding lid for mounting optional TV including comfortable design stool.
43141.01	Wardrobe in saloon on SB side in the front
42414.01	Wall panels in saloon SB, Port and front in cream white HPL.
4.3 FR	ONT CABIN/ SHOWER & HEADS COMPARTMENTS
43021.01	Double berth with slatted base and large drawer
43031.01	Spacious linen-cupboard on Port side
43041.01	Spacious linen cupboard on Starboard side

Linssen 30 SL Sedan

tem	Description	Page 5	
43062.0	O2 Toilet/shower walls FC in high quality Formica wall finishing		
43071.0		n in	
43082.0	Shower in the FC finished in high quality Formica wall finishing and teak seat		
43412.0	Soft paneling FC, longitudinal SB/Port (3 panels)		
5. FINIS	Н		
5.1 L	IGHTING & SOCKETS		
51010.0	LED dimmed interior light fittings in all compartments, with light switches		
51400.0	1x USB socket in the saloon for charging mobil equipment. No data transfer.		
51500.0	1 x 12 V. socket at steering position		
51603.	3 x 230 V. Sockets in the FC (1x) and galley (2x)		
5.2 6	GALLEY		
52015.0	Bar cupboard in saloon, incl. set of Linssen Yachts glasses (comprising: 6 shot glasses, 6 highball glasses, 6 whisky glasses and 6 wine glasses)		
52020.	O2 Integrated waste bucket in cupboard incl. partition with shelves		
52023.	O1 Anti-slip mats in galley		
52030.	O1 Cutlery tray		
52040.	80 l. refrigerator with freezer compartment. The freezer compartment can be remove increase the capacity of the fridge.	d to	
52105.	Gas installation with Campingaz gas bottle (3kg), in container at bathing platform		
52110.	3-burner stainless steel gas hob		
52120.	O2 Glass coverplate for 3-burner gas hob		
52180.	O1 Stainless steel sink		
53020.	Mixer tap in galley type Grohe Essence		
5.3 S	ANITARY FITTINGS		
53010.	O1 Selected bathroom fittings (mirror, toilet paper holder, etc.), in the forward cabin hea	d	
53030.	Wash-basin mixer tap in toilet compartment FC type Grohe Essence		
53050.0	Shower mixer tap in forward shower type Grohe 1000C (Thermostatically adjustable) shower rail	incl.	
53130.	01 Manual sea toilet		
5.4 A	AUDIO / VIDEO/ INTERNET		
54010.0	Stereo radio/MP3-player Fusion RA70N with bluetooth including 2 speakers in the sal and FM radio antenna in mast. Audio streaming possible Operation possible via the App FUSION link AM/FM including RDS Amplifier Class-AB 4x 50W	oon	
5.6 II	NTERIOR UPHOLSTERY		
56031.0	,		
56045.0	Comfortable helm seat finished in Mocka Rock		
56073.0	Design stool finished in Mocka Rock		
56101.	11 Mattrass 1x 2 pers. in front cabin type coldfoam 14 cm. with layer in foam in two hardness grades.		

Linssen Yachts Standard Equipment Linssen 30 SL Sedan

Item	Description	Page	6
56300.0	Curtains for windows and hatches, cream colour		
5.8 EQUIPMENT			
58010.0	Spares kit including tool-kit, impeller, fuses, paint-tip and various maintenance part	:S	
58020.0	Complete inventory including 4 fenders, 4 mooring ropes (10 meters), boathook, lif buoy, bucket, scrubbing brush, national flag, yard ribbon, safety rope for anchor ch and anchor ball		
58030.0	First-aid box in saloon according to DIN13157		
58040.0	ABC fire class compliant fire extinguisher (1 x 2 kg) in saloon		
58045.0	Optical smoke detector with fixed built-in lithium battery (life span 10 years) in all sleeping compartments.		